Polysafe Verona PUR

Polysafe Verona PUR is ideal for use in areas where contaminant spillages can occur, making slip resistance an important consideration. Typical areas include circulation areas and corridors, dining areas and cafes, classrooms, hospital wards, clinics, laundry and sluice rooms, nursing homes, washrooms, WCs, bar serveries, food preparation areas, canteens and institutional applications. For continually wet areas please refer to our Polysafe Hydro, Hydro Evolve or Quattro ranges.



	EN 428/ISO 24346	2.0mm
Roll Size	EN 426/ISO 24341	2m x 20m = 40m ²
Total Weight	EN 430/ISO 23997	2600g/m ²
General Performance	EN 13845 ASTM F1303	Conforms Conforms
Use Area	EN 685/ISO 10874	
Resistance to Chemicals	EN 423	Good chemical resistance
Reaction to Fire	EN 13501-1 ASTM E648 Aus NCC Spec C1.10-3	Class BfI-S1 Class 1 Complies
Abrasion Resistance	EN 13845 EN 649	50,000 cycles Group T
Enhanced Slip Resistance		ESf P3 R10 R10 ≥36 (wet test - 4S Rubber/Slider 96) Rz ≥20µm products is sustainable throughout the guaranteed life SE Guidelines. For further clarification regarding slip
Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
VOC Emissions	AgBB VOC test GBCA/NZGBC Green Star IEQ-VOC Floorscore Finnish M1 Classification	Pass Compliant Certified Certified
Responsible Sourcing	BES 6001	Excellent
	has been independently assessed by the British Boa proper maintenance, the appearance, colour and sli	ard of Agrément and product performance is assured for ip resistance will be retained during this period.
education and healthcare and is GreenTag LCA		772) in the Green Guide to Specification in use areas such Generic EN 15804 Environmental Product Declaration (EP floor scheme. Visit www.polyflor.com/sustainability
	a high quality, cross-linked polyurethane reinforcem arance retention. As with all Polysafe products, Polys	ent, UV cured to provide superior cleaning benefits, life safe Verona PUR should not have a polish applied.
		ic flooring solution which can be confidently cleaned in e implementation of an effective cleaning regime is the
and are suitable for steam cleaning on a period adhesives, maintenance, applications, chemica email tech@polyflor.com. As with all Polysafe products, Polysafe Verona	dic basis. Chemical resistance charts available on rec I resistance and product warranty, consult Polyflor C PUR should not have a polish applied. inting. For latest information, please visit our websit	use with the most commonly used alco-based hand gels quest. For information regarding handling and installation Customer Technical Services on +44 (0)161 767 1912, or e polyflor.com.
100% RECYCLABLE CONTAINS RECYCLED MATERIAL		

 Polyflor UK
 Sales Direct: +44 (0)161 767 1122
 Export Sales Direct: +44 (0)161 767 1913

 Sample Requests: +44 (0)161 767 2551
 email: info@polyflor.com
 www.polyflor.com



Polyflor Australia Tel: 1800 777 425 • email: sales@polyflor.com.au • www.polyflor.com.au Polyflor New Zealand Tel: 0800 765 935 • email: sales@polyflor.co.nz • www.polyflor.co.nz



FLOORING

fames Halitead"